

ODB - Mode 6 Data

SIM 271DE20

MID (hex)	TID (hex)	UID (hex)	Unit	Description
1	83	4		Exhaust Gas Sensor Monitor Bank 1 - Sensor 1
1	84	4		Exhaust Gas Sensor Monitor Bank 1 - Sensor 1
1	8E	84		Exhaust Gas Sensor Monitor Bank 1 - Sensor 1
1	8F	84		Exhaust Gas Sensor Monitor Bank 1 - Sensor 1
2	85	B1	mV/s	Exhaust Gas Sensor Monitor Bank 1 - Sensor 2
2	8D	8B	V	Exhaust Gas Sensor Monitor Bank 1 - Sensor 2
2	86	B1	mV/s	Exhaust Gas Sensor Monitor Bank 1 - Sensor 2
21	90	5		Catalyst Monitor Bank 1
35	B8	1C	°	VVT Monitor Bank 1
35	B9	1C	°	VVT Monitor Bank 1
35	BA	1C	°	VVT Monitor Bank 1
35	BB	1C	°	VVT Monitor Bank 1
39	A7	FE	Pa	EVAP Monitor (Cap Off, 0.150")
3A	A2	FE	Pa	EVAP Monitor (0.090")
3B	A4	3		EVAP Monitor (0.040")
3C	A6	3		EVAP Monitor (0.020")
3D	A8	FE	Pa	Purge Flow Monitor
3D	B6	FE	Pa	Purge Flow Monitor
41	C1	16	°C	Exhaust Gas Sensor Heater Monitor Bank 1 - Sen
42	C4	14	kOhm	Exhaust Gas Sensor Heater Monitor Bank 1 - Sen
A1	0C	24	counts	Misfire Monitor General Data
A2	0C	24	counts	Misfire Cylinder 1 Data
A2	0B	24	counts	Misfire Cylinder 1 Data
A3	0C	24	counts	Misfire Cylinder 2 Data
A3	0B	24	counts	Misfire Cylinder 2 Data
A4	0C	24	counts	Misfire Cylinder 3 Data
A4	0B	24	counts	Misfire Cylinder 3 Data
A5	0C	24	counts	Misfire Cylinder 4 Data
A5	0B	24	counts	Misfire Cylinder 4 Data